AUTOMOTIVE RANGE

SCALPEX NC 17 GEL

TOP

QUALITY -

SUPER STRIPPING GEL WITH NO METHYLENE CHLORIDE.



PRODUCT BENEFITS

- VOC content: 840 g / L.
- May be painted again after brushing or scraping.
- Does not darken wood.
- Gel formula, suitable for vertical surfaces.



- 1,000 L container
- 210 L barrel
- 20 L: 24 x 20 L pallet
- 5 L: 96 x 5 L pallet

AREAS OF APPLICATION

SCALPEX NC 17 has been specially designed in line with Directive 2004/42/CE, the aim of which is to limit the total volatile organic compound (VOC) content of certain vehicle varnishes, paints and refinishing products.

APPLICATION

1.DILUTION: Product is ready to use.

2.APPLICATION EQUIPMENT: Suitable sprayer or cloth.

3.MODE OF OPERATION : Shake well before use, then apply to the surface to be stripped and scrape off dry residue. Can also be used by dipping or spreading over the surface.

<u>4.APPLICATION TEMPERATURE</u>: 5 °C to 50 °C. Effectiveness is reduced at extreme temperatures.

<u>5. TOOL CLEANING</u> Clean tools with water straight after application.

6. YIELD: 100 to 200 ml / m² depending on the way in which it is used.

<u>7. STORAGE</u>: Store product in frost-free premises, away from the elements and direct sunlight. Do not store at temperatures < 5 °C.

* Yield information is only provided as a rough guide. This information is useful to determine the amount needed for the work. This information is in no way contractual. The exact quantity of product to be applied can only be established through tests, based on the different surfaces to be treated.

Technical Data Sheet • May 2021 Page 1/2



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.



PHYSICO-CHEMICAL FEATURES

- Stripping gel
- Orange-coloured gel
- Density: 0.93 g / cm3 at 20 °C
- pH: 6 Frost-proof Flash point: -10 °C



<u>1. PROTECTION OF SURFACES</u>: Do not apply to plastic surfaces.

<u>2. PROTECTION OF PERSONS:</u> Wear suitable gloves, safety goggles and breathing apparatus. Avoid contact with eyes. In the event of splashing, rinse with water. Work in well-ventilated premises. This product is easily flammable.

Important: The contents of this document stem from our experience with the product. We cannot be held liable as far as its use is concerned in every individual case. Given the particular characteristics of each surface (wear and tear, alteration of the entire surface and/or its properties, chemical composition etc.), and to avoid any damage to the surface being treated, it is essential that the Scalp product be tested on a small area to be treated, by following the procedure for application, in order to ensure that no alteration occurs.



