

SCALP FACANET PAE

**HEAVY-DUTY CLEANER & SCOURER
CLEANS BLACK, RED AND GREEN DIRT
NO-RINSE, CHLORINE-FREE PRODUCT FOR FACADES, ROOFS, WALLS
AND OUTDOOR FLOORS**



PRODUCT BENEFITS



- Sprayable
- Deep-acting, removes all types of soiling: atmospheric pollution, black, red and green dirt
- Rinse-free and re-coatable after 48 hours
- Chlorine-, caustic- and potassium-free
- Low odour
- No rinsing
- VOC-free



PACKAGING :

- 20 litres: pallet of 24 X 20 litres
- 5 litres: carton of 4 X 5 litres

AREAS OF APPLICATION

SCALP FACANET PAE is specially designed for effective scouring and cleaning of facades, roofs, walls and outdoor floors. It is ideal for surfaces made of stone, brick, cement, fibrocement, concrete, hydraulic and organic plaster, etc. that have been soiled by urban air pollution (soot deposits, dust, fine particles). It also removes red, black and green dirt that has accumulated on the surface of materials.

Using this product, you can restore facades, roofs, walls and floors to their original condition.

APPLICATION

1. DILUTION: SCALP RENOV' EXPRESS is ready to use.

2. TOOLS: Equipment in nylon or synthetic fibre: Roller, brush, paintbrush. Can be sprayed with appropriate equipment: manual or electric sprayer and airless spray gun (contact our Sales Department).

3. METHOD: Mix SCALP RENOV'EXPRESS well, then apply to the facade to be treated from bottom to top. Allow to act. No need to rinse unless repainting or water-repellent application, or wet effect beyond 48 hours (see our sales department). Repeat if necessary. For application on lime or hydraulic coatings, consult our sales department.

4. APPLICATION TIME: Two to several hours according to the degree of pollution.

5. APPLICATION TEMPERATURE: From 5 to 50°C. Effectiveness is reduced at extreme temperatures.



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

6. CLEANING OF TOOLS : Clean tools in water immediately after use.

7. APPLICATION RATE: From 150 to 250 ml /m2 environ.*.

8. STORAGE : Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

PHYSICOCHEMICAL PROPERTIES

- Sodium Hypochlorite based aqueous product
- Yellowish liquid
- Density : 1.16 +/- 0.03 g /cm³ at 20°C
- pH : >13
- Not frost resistant
- Flash point : N/A

APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Protect zinc, aluminum, galva, copper, PVC, upholstery, metal or painted surfaces and surrounding vegetation. Protect all surfaces that are not to be cleaned. It is advisable to carry out preliminary tests on all substrates before applying the product.

CAUTION: On hydraulic coatings, crumbling of the plaster may occur. In this case, we recommend thorough remineralization and rinsing of the substrate after application of the product.

2. PROTECTION OF PERSONS: This is a corrosive product. Wear appropriate protective equipment and clothing. Avoid contact with skin and eyes. Wash immediately and abundantly with water in case of contact. Do not inhale fumes and do not mix with acids. Do not pour the product or its waste into rivers or watercourses.

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

Technical Data Sheet • August 2024
Page 2/2